

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Currently Amended) A method of transmitting ~~a packet data to which a sync pattern is added before transmission~~data packets, said method comprising the steps of:

(a) generating a fixed pattern comprising 'm' words ('m' is an integer greater than 0);

(b) generating variable, non-random. patterns of predetermined bit structure, each pattern comprising 'n' words ('n' is an integer greater than 1);

(c) generating ~~a sync patterns~~ comprising 'q' words ('q' = m + n), each of the sync patterns formed by combining the fixed pattern and one of the variable patterns;

(d) ~~controlling said step (c) for making a bit structure included in at least two~~adding one of said sync patterns to each of said data packets in a data stream, wherein consecutive ones of said data packets include each have added respectively different types of variable patterns.

2. (Previously Presented) The method as defined in Claim 1, wherein the variable pattern comprises a plurality of words, and the variable patterns are made by changing an order of the words.

3. (Original) The method as defined in Claim 1, wherein the fixed pattern comprises three words.

4. (Original) The method as defined in Claim 3, wherein the three words includes 'eb', 'cb' and 'aa', expressed in a hexadecimal notation.

5. (Original) The method as defined in Claim 1, wherein the variable pattern comprises five words.

6. (Original) The method as defined in Claim 5, wherein the five words includes '4c', 'ea', 'cd', '7a' and '81', expressed in a hexadecimal notation.

7. (Previously Presented) The method as defined in Claim 1, wherein the variable patterns are '4ceacd7a81' and 'cd7aea814c' expressed in a hexadecimal notation.

8. (Original) The method as defined in Claim 1, wherein the packet data is a digital video signal.

9. (Previously Presented) The method as defined in Claim 8, wherein the digital video signal is a compressed signal.

10. (Previously Presented) The method as defined in Claim 9, wherein the compressed signal is a DIF stream.

11. (Original) The method as defined in Claim 1, wherein the packet data is transmitted through an ATM transmission line.

12. (Original) A method of receiving a packet data transmitted by the method defined in Claim 1, said method including a step of detecting a sync.

13. (Original) A method of receiving a packet data transmitted by the method defined in Claim 1, said method including the steps of:

(a) detecting a sync for examining both of a fixed pattern and a variable pattern of a data received; and

(b) securing a sync for examining only the fixed pattern,

wherein said step (a) processes the data until the sync is secured, and said step (b) processes the data after the sync is secured.

14. (Currently Amended) A packet data transmitting apparatus for ~~adding a sync pattern to a packet data before transmitting the data~~ packets, said transmitting apparatus comprising:

(a) means for generating a fixed pattern comprising 'm' words ('m' is an integer greater than 0);

(b) means for generating variable, non-random patterns of predetermined bit structure, each pattern comprising 'n' words ('n' is an integer greater than 1);

(c) means for generating ~~a sync patterns~~ comprising 'q' words ('q' = m + n), each of the sync patterns formed by combining the fixed pattern and one of the variable patterns; and

(d) means for ~~controlling said means defined in (c) for making a bit structure included in at least two~~ adding one of said sync patterns to each of said packets in a data stream, wherein consecutive ones of said data packets include each have added respectively different types of variable patterns.

15. (Previously Presented) A packet data receiving apparatus for receiving the packet data transmitted by the method defined in Claim 1, said receiving apparatus comprising:

(a) means for detecting a sync for examining both of a fixed pattern and a variable pattern of a data received; and

(b) means for securing a sync for examining only the fixed pattern,

wherein said means defined in (a) processes the data until the sync is secured, and said means defined in (b) processes the data after the sync is secured.

16. (Previously Presented) A method as defined in Claim 1, wherein the packet data comprises a plurality of blocks, and the blocks include 's' words having a block header of 'm' words, said method further comprising the step of:

adding a transmission header of ' $s \times k$ ' words (k is a natural number),

wherein the transmission header is divided into ' k ' pieces of blocks at intervals of every 's' words, each block of said ' k ' pieces of blocks includes the fixed pattern of 'm' words at a top thereof, the fixed pattern employs a pattern other than patterns used in the block header.